

TIE DOWN

MANUFACTURING INGENUITY

PX3

Penetrating Mobile Fall Protection Unit

The PX3 mobile fall protection system offers unparalleled portability while being 45% lighter than others on the market at 430 lbs. The PX3 lifts into place, allowing the users to quickly click off and get to work. When the work moves, the PX3 can quickly be relocated. Handling up to five workers at a time, three in fall arrest and two in fall restraint, this "best-in-class" solution ships job site ready on a standard pallet.

Part ID: 72810



PX3

Demo
Video



COMPLIANCE: OSHA 1910.140 & 1926.502

Key Features

- For use on TPO, EPDM, metal and built-up roofing
- 5 users: 3 in fall arrest and 2 in fall restraint
- Unit Weight: 430 Lbs.
- Penetrating design
- Area footprint: 40" x 48" shipping jobsite ready
- Includes locking toolbox
- Premium 300 lbs. flat-free tires (1200 lbs. capacity)
- Four lifting rings for rigging

As easy as...

 **LIFT**
to rooftop

 **CLICK**
to anchor points

 **GO**
work safely & securely

CRS
COMMERCIAL
ROOFING
SPECIALTIES
Inc.



800-267-2308

www.crssupply.com

internetsales@crssupply.com

TIE DOWN

MANUFACTURING INGENUITY



THE PX3 **FEATURES 5 STEEL SPIKES** THAT PENETRATE THE ROOF **IN THE EVENT OF A FALL**, ENSURING STABILITY AND FALL ARREST SAFETY. TO RESCUE A FALLEN WORKER, OUR **RESCUE WINCH SYSTEM** OFFERS **100-FEET OF GALVANIZED LIFELINE**, PROVIDING AMPLE LENGTH FOR LIFTING OR LOWERING THE FALLEN WORKER TO SAFETY WITH ITS MANUAL WINCH. REST ASSURED, THESE FEATURES **PROTECT AND RESCUE YOUR WORKERS** IN CASE OF A FALL.

PX3

RESCUE WINCH SYSTEM

Steel Fall Arrest Penetrating Spikes



Rescue Winch Part ID: 72819

Sold Separately



PROTECT YOUR WORKERS WITH PX3

Part ID: 72810